



EP CUBE

More Flexible, More Intelligent Residential Energy Storage System **NEW**



EP Cube is a flexible and intelligent residential energy storage system intended for smart management of solar power generation and residential electricity consumption. Easy to install, the device is available for remote control, with energy capacity at your discretion. Small in size, it is safe and reliable.

FEATURES



Flexible and convenient

Modular battery system makes transport and installation easy.
Capacity options from 6.6 kWh to 19.9 kWh.



Cost-saving

All-in-one design saves installation time and cost.
Automates generation and consumption.



Power guarantee

Automated power supply during grid outage.
High-power electrical appliances continue to function normally if the grid goes down.



Safe and reliable

Lithium iron phosphate batteries.
Meets highest certification standards.
IP 65 Enclosure.



Compatible

Compatible with existing and newly installed PV systems.
Allows up to 16A DC PV input per MPPT.
Compatible with maximum 7.4 kW EV chargers.



Intelligent management

Monitors generation, storage and consumption of electricity in real time.
Automatic weather alerts help actively manage stored capacity.
OTA (Over-The-Air) firmware upgrade.

EP CUBE TECHNICAL SPECIFICATION



EP Cube HES-EU1-706G EP Cube HES-EU1-710G EP Cube HES-EU1-713G EP Cube HES-EU1-716G EP Cube HES-EU1-720G

SYSTEM SPECIFICATION

System components					
Type of inverter	Hybrid bidirectional				
Number of inverters	1				
Number of battery modules	2	3	4	5	6
Base	1				

HYBRID INVERTER

DC Input (PV)	
Max PV input power	10 kWp
MPPTs	2
Number of inputs per MPPT	1
Max input power per MPPT	5 kWp
Max PV input voltage	600 V _{DC}
MPPT voltage range	90 V _{DC} - 550 V _{DC}
Max MPPT input current	16 A
Max MPPT short current	20 A
MPPT start-up voltage	120 V _{DC}

AC On-grid	
Rated AC output voltage	Single phase / L+N+PE / 230 V _{AC}
Rated grid frequency	50 Hz
Max continuous power (battery + PV)	7.6 kW ¹
Max continuous current (battery + PV)	33.0 A
Output power factor	~1 (adjustable from 0.8 leading to 0.8 lagging)
Output THDi	< 5% (rated power)

AC-Boost (back-up) ²	
Rated AC output voltage	Single Phase / L+N+PE / 230 V _{AC}
Rated output frequency	50 Hz
Max continuous power (battery + PV)	7.6 kVA
Max continuous current (battery + PV)	33.0 A
Switching-time	< 30ms ³

LITHIUM-ION BATTERY MODULE

General					
Cell technology	LiFePO4				
Number of battery modules	2	3	4	5	6
Nominal capacity ⁴	6.6 kWh	9.9 kWh	13.3 kWh	16.6 kWh	19.9 kWh
Max continuous power (battery only)	3 kVA	5 kVA	6.5 kVA	7.6 kVA	7.6 kVA
DOD	100% ⁵				
Voltage range	30 V ~ 43.8 V _{DC}				
Nominal voltage	38.4 V _{DC}				
Dimension (WxHxD)	600 x 215 x 165 mm				
Weight	< 35 kg				

EP CUBE TECHNICAL SPECIFICATION

GENERAL PARAMETER

System

Applications	Self consumption / TOU / Backup
Type of inverter	Hybrid bidirectional
Inverter dimension (WxHxD)	600 x 505 x 243 mm
Inverter weight	< 38 kg
Inverter topology	Transformerless

GENERAL PARAMETER

System

DC battery protection	Fuse holder incl. fuses (+/-)				
Dimension (WxHxD)	600 x 1006 x 243 mm	600 x 1221 x 243 mm	600 x 1436 x 243 mm	600 x 1651 x 243 mm	600 x 1866 x 243 mm
System weight	111.5 kg	146.5 kg	181.5 kg	216.5 kg	251.5 kg
Noise	< 30dB				
Enclosure type	IP65				
Cooling type	Natural cooling				
Operating altitude	3,000 m				
Operating relative humidity	95% without condensing				
Operating temperature range	- 20°C to 50°C				
Recommended operating temperature	0°C to 30°C				
Storage temperature	-20°C ~ 50°C less than 1 month / 0°C ~ 35°C up to 1 year ⁶				
Display	LED & APP				
Installation method	Floor mounted (optional: wall mounted)				
Communication interface	WiFi, ethernet, RS485, CAN, I/O, API				

Warranty

Inverter	10 years
Battery ⁷	> 80 % capacity, up to 10 years or 6,000 cycles
Accessories ⁸	2 years

Certifications

Safety	IEC / EN 62109-1, IEC / EN 62109-2, IEC / EN 62477-1, IEC / EN 62619-1, IEC 60730 Annex H, IEC 60529, VDE 2510-50, UN 38.3
EMC	IEC 61000-6-3, IEC / EN 61000-6-1
Energy efficiency	IEC 61683
Grid standards	NTS 2.1 Type (A), UNE 217001, UNE 217002, RD 244, CEI 0-21, VDE-AR-N 4105, DIN VDE V 0124-100, G99 type A, UKCA

ACCESSORIES

Items	Model
EP Cube AC Switch Box	EP CUBE ASB1-40
EP Cube Meter	EP Cube 1PHM1
EP Cube Wall-mount Kit	EP Cube Wall-mount Kit1

Notes

- Rated AC output power is adjustable according to the grid code of each country. (6kW for CEI 0-21; 4.6kW for VDE-AR-N 4105)
- Only in back-up mode in case of grid outage.
- For reactive loads, for active loads is lower.
- Test conditions: 100% depth of discharge (DOD), 0.2C rate charge and discharge at 25°C, at the beginning of life.
- EP Cube will maintain a minimum SOC of 15% during off-grid operation.
- Refer to the installation manual and follow the storage requirements and guidelines.
- Battery capacity warranty up to 10 years or 6000 cycles, (whichever occurs first).
- As per Limited Warranties Statement.

Specifications are subject to change without prior notice. Unauthorized copying and reprinting of this datasheet is prohibited.

Canadian Solar EMEA GmbH Add: Radlkoferstrasse 2, 81373, Munich, Germany
Tel: +49 89 51996890 E-mail: emea.sales@csisolar.com

